

Safety Data Sheet

New Make Whisky Spirit

1. IDENTIFICATION OF THE MATERIAL

Product Name	New Make Whisky Spirit
Chemical Name	Ethanol
Cunonumo	Ex-still Whisky Spirit, Australian New Make Whisky Spirit, Single Malt
Synonyms	New Make Whisky Spirit.
Shipping Name	ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL
	ALCOHOL SOLUTION)
Chemical Formula	C_2H_6O
CAS No	64-17-5
Product Code	WHN-00
Use(s)	Beverage grade alcohol, alcoholic beverages (in suitable dilution),
	foodstuffs.

Supplier Name	Tarac Technologies Pty Ltd
Address	20 Samuel Road, Nuriootpa SA AUSTRALIA 5355
Telephone	+61 8 8568 6500
Fax	+61 8 8562 2031
Emergency	1800 606 911
Email	info@tarac.com.au
Website	https://tarac.com.au/

2. HAZARDS IDENTIFICATION

CLASSIFICATIONS

Classified as hazardous according to NOHSC criteria.

Classified as a dangerous good by the criteria of the ADG code.

UN No	1170	DG Class	3	Subsidiary Risk(s)	None Allocated
Pkg Group	П	Hazchem Code	●2YE	EPG	3A1

GHS CLASSIFICATION

- Flammable liquids (Category 3)
- Eye irritation (Category 2A)





Flammable

SIGNAL WORD

DANGER

HAZARD STATEMENTS

- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.

Doc No: Page No: Issue No: SDS013 1 of 8 002

Issue Date: Approved By: 02/05/2024 Safety Culture Manager



PRECAUTIONARY STATEMENTS

Prevention

- P210 Keep away from heat/sparks/open flames/hot surfaces No smoking.
- P233 Keep container tightly closed.
- P240 Ground/Bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/ lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
- P264 Wash skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

- P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell.
- P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337 + P313 If eye irritation persists: Get medical advice/attention.
- P370 + P378 In case of fire: Use extinguishing media detailed in Section 5 for extinction.

Storage

P403 + P235 - Store in a well-ventilated place. Keep cool.

Disposal

P501 - Dispose of contents/container to hazardous or special waste collection point

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No	Content
ETHANOL	C ₂ H ₆ O	64-17-5	≤ 80.0%
WATER	H ₂ O	7732-18-5	≥ 20.0%

4. FIRST AID MEASURES

GENERAL ADVICE

Show this safety data sheet to the doctor in attendance.

IN CASE OF EYE CONTACT

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Doc No: Page No: Issue Date: Approved By:

SDS013 2 of 8 002 02/05/2024 Safety Culture Manager



IN CASE OF SKIN CONTACT

- Immediately remove all contaminated clothing, including footwear
- Flush skin and hair with running water (and soap if available)
- Seek medical attention in event of irritation.

IF INHALED

- If fumes or combustion products are inhaled remove from contaminated area into fresh air
- Seek medical advice.

IF SWALLOWED

- If swallowed do NOT induce vomiting.
- Immediately make person drink water (not more than 2 glasses)
- Seek medical advice.

5. FIREFIGHTING MEASURES

SUITABLE EXTINGUISHING EQUIPMENT

- Alcohol stable foam
- Dry chemical powder
- BCF (where regulations permit)
- Carbon dioxide
- Water spray or fog large fires only

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

- Highly flammable and forms explosive mixtures in air at ambient temperatures.
- May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.
- Do not expose to heat or ignition sources.
- Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights, mobile phones etc.
- Earth containers when dispensing fluids.
- Vapours are heavier than air and may spread along the floor.
- Beware of flashback.

ADVICE FOR FIREFIGHTERS

 Stay in danger area only if wearing self-contained breathing apparatus. Prevent skin contact by keeping safe distance or by wearing suitable protective clothing.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Advice for non-emergency personnel: Do not breathe vapours, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

ENVIRONMENTAL PRECAUTIONS

Do not let product enter drains. Risk of explosion.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

 Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material. Dispose of properly. Clean up affected area.

7. STORAGE & HANDLING

Doc No: Page No: Issue No: Issue Date: Approved By:

SDS013 3 of 8 002 02/05/2024 Safety Culture Manager



PRECAUTIONS FOR SAFE HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- DO NOT allow clothing wet with material to stay in contact with skin · Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights, heat or ignition sources.
- When handling, DO NOT eat, drink or smoke
- Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- Keep containers securely sealed.
- Store away from incompatible materials in a cool, dry well-ventilated area.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storage and handling recommendations contained within this SDS.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE STANDARDS

- ETHANOL (64-17-5)
- ES-TWA: 1000 ppm (1880 mg/m3)
- WES-TWA: 1000 ppm (1880 mg/m3)

ENGINEERING CONTROLS

Ensure adequate natural ventilation. Flammable/explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back.

INDIVIDUAL PROTECTION MEASURES

EYE & FACE PROTECTION

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.
- In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable.

BODY PROTECTION

- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber
- Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

Doc No: Page No: Issue No: Issue Date: Approved By: SDS013 4 of 8 002 02/05/2024 Safety Culture Manager



- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.

RESPIRATORY PROTECTION

- Required when vapours/aerosols are generated.
- Recommendations on filtering respiratory protection are based on standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system

OTHER PROTECTION

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Ensure there is ready access to a safety shower.
- For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).
- Non sparking safety or conductive footwear.
 Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended.

9. PHYSICAL & CHEMICAL PROPERTIES

Appearance	Clear colourless liquid	Solubility (water)	Soluble
Odour	Slight odour	Specific Gravity	0.887
рН	NOT AVAILABLE	% Volatiles	NOT AVAILABLE
Vapour Pressure	5.9 hPa @ 20°C	Flammability	Highly flammable
Vapour Density	NOT AVAILABLE	Flash Point	13°C
Boiling Point	78.3°C	Upper Explosion Limit	19 %
Melting Point	-130 to -114.1	Lower Explosion Limit	3.3 %
Evaporation Rate	2.53 BuAC = 1	Autoignition Temperature	365°C

10. STABILITY & REACTIVITY

REACTIVITY

Vapours may form explosive mixture with air

CHEMICAL STABILITY

 Reacts with air to form peroxides. The product is chemically stable under standard ambient conditions (room temperature)

POSSIBILITY OF HAZARDOUS REACTIONS

No data available

CONDITIONS TO AVOID

Warming

INCOMPATIBLE MATERIALS

Doc No: Page No: Issue No: Issue Date: Approved By: SDS013 5 of 8 002 02/05/2024 Safety Culture Manager



 Aluminium, Acids, Oxidizing agents, Alkali metals, Halogenated compounds, Ammonia, Acid chlorides, Acid anhydrides, Reducing agents, Peroxides

HAZARDOUS DECOMPOSITION PRODUCTS

• In the event of fire, see Section 5

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

- Oral: No data available
- Symptoms: Possible symptoms mucosal irritations
- Dermal: No data available

SKIN CORROSION/IRRITATION

No data available

SERIOUS EYE DAMAGE/IRRITATION

Mixture causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

No data available

GERM CELL MUTAGENICITY

No data available

CARCINOGENICITY

No data available

REPRODUCTIVE TOXICITY

No data available

SPECIFIC TARGET ORGAN TOXICITY (STOT)—SINGLE EXPOSURE

Mixture may cause damage to organs -eyes, central nervous system

SPECIFIC TARGET ORGAN TOXICITY (STOT)—REPEATED EXPOSURE

No data available

ASPIRATION HAZARD

No data available

OTHER INFORMATION

To the best of Tarac's knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated., Central nervous system depression, Gastrointestinal disturbance, Nausea, Dizziness, Headache, narcosis, May cause convulsions. Other dangerous properties cannot be excluded. Handle in accordance with good industrial hygiene and safety practice

12. ECOLOGICAL INFORMATION

ECOTOXICITY

No data available

PERSISTENCE AND DEGRADABILITY

Doc No: Page No: Issue No: Issue Date: Approved By:

SDS013 6 of 8 002 02/05/2024 Safety Culture Manager



No data available

BIOACCUMULATIVE POTENTIAL

No data available

MOBILITY IN SOIL

No data available

OTHER ADVERSE EFFECTS

No data available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

No special precautions are required for the disposal of this product.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOODS BY THE CRITERIA OF THE ADG CODE

NOT A MARINE POLLUTANT

LAND TRANSPORT ADG

Shipping	ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)				
Name					
UN No	1170	DG Class	3	Subsidiary Risk(s)	None Allocated
Pkg Group	Ш	Hazchem Code	●2YE	EPG	3A1
Limited Qty	1 Litre			Special Provisions	144

MARITIME TRANSPORT IMDG

Shipping	ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)				
Name					
UN No	1170	IMDG Class	3	Subsidiary Risk(s)	None Allocated
Pkg Group	Ш	Hazchem Code	●2YE	EMS No	F- E, S- D
Limited Qty	1 Litre			Special Provisions	144

AIR TRANSPORT (/DGR)

, ,					
Shipping	ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)				
Name					
UN No	1170	ICAO-IATA Class	3	Subsidiary Risk(s)	None Allocated
Pkg Group	Ш	Hazchem Code	●2YE	ERG Code	3
Cargo Only	364	Cargo Only Max	60	P&C Limited Ins	Y341
Cargo Only		Cargo Offig Wax	Litre	r & C Lillilled IIIs	
Pass & Cargo	353	Pass & Cargo	5 Litre	P&C Limited Qty	1 Litre

15. REGULATORY INFORMATION

SAFETY HEALTH AND ENVIRONMENTAL REGULATIONS

A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

REGULATORY LISTS

Doc No: Page No: Issue No: Issue Date: Approved By:

SDS013 7 of 8 002 02/05/2024 Safety Culture Manager



- Australian Exposure Standards
- Australian Inventory of Chemical Substances (AICS)
- Australian Hazardous Substances Information System Consolidated Lists

16. OTHER INFORMATION

ABBREVIATIONS

- mg/m3 Milligrams per cubic metre
- ppm Parts Per Million
- TWA/ES Time Weighted Average or Exposure Standard.
- NOS Not Otherwise Specified
- pH relates to hydrogen ion concentration this value will relate to a scale of 0 14, where 0 is highly acidic and 14 is highly alkaline.
- CAS# Chemical Abstract Service number to uniquely identify chemical compounds.
- PC—TWA: Permissible Concentration-Time Weighted Average
- PC—STEL: Permissible Concentration-Short Term Exposure Limit
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit。
- IDLH: Immediately Dangerous to Life or Health Concentrations
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: Bio-Concentration Factors
- BEI: Biological Exposure Index

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES

The recommendation for protective equipment contained within is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

All information given by Tarac Technologies Pty Ltd is offered in good faith and is true and accurate to the best of our knowledge. However, since conditions of use are beyond our control, all information relative to usage is offered without warranty or guarantee and should not be construed as a recommendation to use any of our products in breach of any provisions of any Federal or State Acts or Regulations.

In particular, the information contained herein should not be construed as a representation that the product is suitable for any particular purpose or application.

End of Report

Doc No: Page No: Issue Date: Approved By:

SDS013 8 of 8 002 02/05/2024 Safety Culture Manager

